



The Audio Point Product offer the Highest level of performance and Trouble free experience. Our engineers have optimized each Products to ensure each product Operates to its fullest potential for longer time.

*Thankyou for purchasing this genuine Audio Point Product.*

**Thank you**  
FOR YOUR PURCHASE

**AP AUDIO POINT** **2226-CS**

Triple-roll surround and straight cone

|                   |             |
|-------------------|-------------|
| Nominal Diameter  | 381mm/15"   |
| Magnet Type       | Ferrite     |
| Voice Coil Dia.   | 99.3mm/4"   |
| Coil Material     | Copper I/O  |
| Power Rating      | 600 W (RMS) |
| Nominal Impedance | 8 Ohms      |
| Surround material | Cloth       |
| Sensitivity       | 97 dB       |
| Frequency Range   | 49-2000 Hz  |
| Suspension        | Single      |
| Cone material     | Paper       |

**AP AUDIO POINT** **15 SD-500**

The 15 SD-500 is designed to provide an excellent frequency response linearity with very low distortion.

|                     |                 |
|---------------------|-----------------|
| Nominal Diameter    | 381 mm/15"      |
| Power Rating        | 500 W (RMS)     |
| Nominal Impedance   | 8 Ohm           |
| Sensitivity         | 97 dB           |
| Frequency Range     | 45-3500 Hz      |
| Voice Coil Diameter | 82.5 mm/3.25"   |
| Coil Material       | Italian copper  |
| Cone Material       | Malaysian Paper |
| Surround Material   | Cloth           |
| Suspension          | Single          |
| Chassis Type        | Aluminum        |
| Magnet Type         | Ferrite         |

**AP AUDIO POINT** **BW-500X**

THE BW-500X FEATURES WITH DOUBLE MAGNET AND ITALIAN VOICE COIL SYSTEM ENSURES EXCELLENT POWERFUL BASS CONTROL

|                   |                    |
|-------------------|--------------------|
| Nominal Diameter  | 381mm/15"          |
| Magnet Type       | Ferrite            |
| Voice Coil Dia.   | 76.2mm/3"          |
| Coil Material     | Italian Copper I/O |
| Power Rating      | 500 W (RMS)        |
| Nominal Impedance | 8 Ohms             |
| Surround material | Cloth              |
| Sensitivity       | 98 dB              |
| Frequency Range   | 45-3500 Hz         |
| Suspension        | single             |
| Cone material     | Paper              |

**AP AUDIO POINT** **15" Titanium series 15-TBW-650G**

The 15-TBW-650G is well suited for both live sound and recorded music venues.

|                   |             |
|-------------------|-------------|
| Nominal Diameter  | 381mm/15"   |
| Magnet Type       | Ferrite     |
| Voice Coil Dia.   | 99.3mm/4"   |
| Power Rating      | 600 W (RMS) |
| Nominal Impedance | 8 Ohms      |
| Surround material | Cloth       |
| Sensitivity       | 97 dB       |
| Frequency Range   | 49-2500 Hz  |
| Suspension        | Single      |
| Cone material     | Paper       |

**AP AUDIO POINT** **15" SONET-500GM15**

THE SONET-500GM15 IS DESIGNED TO PROVIDE AN EXCELLENT FREQUENCY RESPONSE LINEARITY WITH VERY LOW DISTORTION.

|                   |             |
|-------------------|-------------|
| NOMINAL DIAMETER  | 381MM/15"   |
| MAGNET TYPE       | FERRITE     |
| VOICE COIL DIA.   | 82.5MM      |
| COIL TYPE         | IN/OUT      |
| POWER RATING      | 500 W (RMS) |
| NOMINAL IMPEDANCE | 8 OHMS      |
| SURROUND MATERIAL | CLOTH       |
| SENSITIVITY       | 98 DB       |
| FREQUENCY RANGE   | 49-3000 HZ  |
| SUSPENSION        | SINGLE      |
| CONE MATERIAL     | PAPER       |

**AP AUDIO POINT** **15"**

Ideal for high level response in both live sound and recorded music venues. professional Loudspeaker

|                   |                 |
|-------------------|-----------------|
| Nominal Diameter  | 381mm/15"       |
| Magnet Type       | Ferrite         |
| Voice Coil Dia.   | 76.2/3"         |
| Coil Material     | Italian CCA I/O |
| Power Rating      | 400 W (RMS)     |
| Nominal Impedance | 8 Ohms          |
| Surround material | Cloth           |
| Sensitivity       | 97 dB           |
| Frequency Range   | 55-2000 Hz      |
| Suspension        | Single          |
| Cone material     | Paper           |

**AP AUDIO POINT** **MB-300CS** **12"**

High power 12" woofer. Very good power handling, excellent and very low distortion.

|                   |                |
|-------------------|----------------|
| Nominal Diameter  | 320mm/12"      |
| Magnet Type       | Ferrite        |
| Voice Coil Dia.   | 76.2/3"        |
| Coil Material     | Italian Copper |
| Power Rating      | 300 W (RMS)    |
| Nominal Impedance | 8 Ohms         |
| Surround material | Cloth          |
| Sensitivity       | 97 dB          |
| Frequency Range   | 55-2500 Hz     |
| Suspension        | Single         |
| Cone material     | Paper          |

**AP AUDIO POINT** **12NC-400H3**

High efficiency 12" mid-bass. Very high sensitivity, excellent linearity and very low distortion.

|                   |              |
|-------------------|--------------|
| Nominal Diameter  | 320mm/12"    |
| Magnet Type       | Ferrite      |
| Voice Coil Dia.   | 76.2mm/3"    |
| Coil Material     | Italian CCAW |
| Power Rating      | 400 W (RMS)  |
| Nominal Impedance | 8 Ohms       |
| Surround material | Cloth        |
| Sensitivity       | 98 dB        |
| Frequency Range   | 55-4000 Hz   |
| Suspension        | Single       |
| Cone material     | Paper        |

**AUDIO POINT** **BH-15WY-500** **15"**

High power 15" woofer. Very good power handling, excellent linearity and very low distortion.

|                     |                       |
|---------------------|-----------------------|
| Nominal Diameter    | 381 mm/15 in          |
| Power Rating        | 400 W (AES)           |
| Impedance           | 8 Ohm                 |
| Sensitivity         | 97 dB                 |
| Suspension          | Single                |
| Paper Cone Material | - MALAYSIAN           |
| Surround Material   | - CLOTH               |
| Voice Coil Diameter | - 76.2 / 3 in         |
| Coil Material       | - ITALIAN COPPER WIRE |
| Magnet Type         | - FERRITE             |
| Chassis Type        | - ALUMINUM            |
| Kind of Layers      | - INSIDE/OUTSIDE      |
| Frequency Range     | - 55-2000 Hz          |

**AP AUDIO POINT** **15"** **DZIRE-400MB**

High power 15" woofer. Very good power handling, excellent and very low distortion.

|                   |                  |
|-------------------|------------------|
| Nominal Diameter  | 381mm/15"        |
| Magnet Type       | Ferrite          |
| Voice Coil Dia.   | 76.2/3"          |
| Coil Material     | Italian wire I/O |
| Power Rating      | 400 W (RMS)      |
| Nominal Impedance | 8 Ohms           |
| Surround material | Cloth            |
| Sensitivity       | 97 dB            |
| Frequency Range   | 40-3000 Hz       |
| Suspension        | Single           |
| Cone material     | Paper            |

**AP AUDIO POINT** **CS-12AX-200**

**12" Professional PA speaker**

Italian voice coil gives you more power.

The CS-12AX-200 Suitable for bass, midrange and monitoring applications.

|                     |                     |
|---------------------|---------------------|
| Nominal Diameter    | 305mm (12")         |
| Power Rating        | 200 W (AES)         |
| Sensitivity         | 97dB                |
| Nominal Impedance   | 8 Ohms              |
| Frequency Range     | 45Hz- 3500Hz        |
| Chassis Type        | Heavy Duty Steel    |
| Magnet Type         | Ferrite             |
| Voice coil Diameter | 51.2mm/2 in         |
| Cone Material       | Paper               |
| Surround Material   | Cloth               |
| Coil Material       | Italian Copper Wire |

**AP AUDIO POINT** **12" PROFESSIONAL LOUDSPEAKER** **MB-400HF**

|                   |             |
|-------------------|-------------|
| Nominal Diameter  | 320mm / 12" |
| Magnet Type       | Ferrite     |
| Voice Coil Dia.   | 76.2mm / 3" |
| Power Rating      | 400 W (RMS) |
| Nominal Impedance | 8 Ohm       |
| Cone Material     | Paper       |
| Surround Material | Cloth       |
| Sensitivity       | 99.0 dB     |
| Frequency Range   | 55-4000 Hz  |
| Suspension        | Single      |

**THE MB-400HF FEATURES A LARGE 3 INCH ITALIAN VOICE COIL PRODUCE EXTREMELY HIGH SOUND PRESSURE.**

**AUDIO POINT** **MB-15G-300**

**15" professional Loudspeaker**

Excellent low and mid frequency response.

|                      |             |                  |
|----------------------|-------------|------------------|
| NOMINAL DIAMETER-    | 380mm/15".  | Surround - CLOTH |
| POWER RATING-        | 300 W (AES) |                  |
| NOMINAL IMPEDENCE-   | 8 Ohm       |                  |
| VOICE COIL DIAMETER- | 76.2 mm/3"  |                  |
| COIL MATERIAL-       | COPPER -W   |                  |
| SENSITIVITY-         | 97 dB       |                  |
| FREQUENCY RANGE-     | 45-3500 Hz  |                  |
| CHASSIS TYPE-        | ALUMINUM    |                  |
| MAGNET TYPE-         | FERRITE     |                  |
| SUSPENSION-          | SINGLE      |                  |
| CONE MATERIAL-       | PAPER       |                  |

**AP AUDIO POINT** **MB-15G1-500**

The AUDIO POINT MB-15G1-500 will produce extremely high sound pressure in low and mid frequencies.

|                     |                 |
|---------------------|-----------------|
| Nominal Diameter    | 381 mm/15"      |
| Power Rating        | 400 W (RMS)     |
| Nominal Impedance   | 8 Ohm           |
| Sensitivity         | 97 dB           |
| Frequency Range     | 40-3000 Hz      |
| Voice Coil Diameter | 76.2 mm/3"      |
| Coil Material       | Italian copper  |
| Cone Material       | Malaysian Paper |
| Surround Material   | Cloth           |
| Suspension          | Single          |
| Chassis Type        | Cast Aluminum   |
| Magnet Type         | Ferrite         |



**AP AUDIO POINT** **21"** **21SW-2500**

THE 21SW-2500 IS A VERY HIGH POWER HANDLING AND EFFICIENCY TRANSDUCER SPECIALLY PROVIDE VERY POWERFUL BASS.

|                   |                 |
|-------------------|-----------------|
| NOMINAL DIAMETER  | 530MM/21"       |
| MAGNET TYPE       | FERRITE(4 CUT)  |
| VOICE COIL DIA.   | 152MM/ I/O      |
| COIL MATERIAL     | MALYSIAN COPPER |
| POWER RATING      | 2500W (RMS)     |
| NOMINAL IMPEDANCE | 8 OHMS          |
| SURROUND MATERIAL | CLOTH           |
| SENSITIVITY       | 97 DB           |
| FREQUENCY RANGE   | 30-1000 HZ      |
| SUSPENSION        | DOUBLE          |
| CONE MATERIAL     | PAPER           |

**AP AUDIO POINT** **18L-2000-Y**

Malaysian original paper cone and Italian voice coil gives you Lion performance.

|                   |                  |  |
|-------------------|------------------|--|
| Nominal Diameter  | 487mm/18"        | The 18L-2000-Y is a very high power handling and efficiency transducer specially designed to provide powerful and accurate sub-bass frequencies with low distortion and low power compression. |
| Magnet Type       | Ferrite (4 cut ) |  |
| Voice Coil Dia.   | 126mm/5" I/O     |  |
| Coil Material     | Italian Copper   |  |
| Power Rating      | 2000 W (RMS)     |  |
| Nominal Impedance | 8 Ohms           |  |
| Surround material | Cloth            |  |
| Sensitivity       | 96 dB            |  |
| Frequency Range   | 30-1500 Hz       |  |
| Suspension        | Double Silicone  |  |
| Cone material     | Malaysian Paper  |  |

**AP AUDIO POINT** **CF-1600LF**

The CF-1600LF uses a fibre loaded cone for high quality performance.

|                   |                  |
|-------------------|------------------|
| Nominal Diameter  | 457mm/18"        |
| Magnet Type       | Ferrite          |
| Magnet Size       | 256x25mm         |
| Voice Coil Dia.   | 114.4mm/4.5" I/O |
| Coil Material     | Italian Copper   |
| Power Rating      | 1600 W (AES)     |
| Nominal Impedance | 8 Ohms           |
| Surround material | Cloth            |
| Sensitivity       | 97 dB            |
| Frequency Range   | 30-1500 Hz       |
| Suspension        | Double Silicone  |
| Cone material     | Malaysian Paper  |

**AP AUDIO POINT** **15"** **15-GR-400**

High power 15" woofer. Very good power handling, excellent and very low distortion.

|                   |                  |
|-------------------|------------------|
| Nominal Diameter  | 381mm/15"        |
| Magnet Type       | Ferrite          |
| Voice Coil Dia.   | 76.2/3"          |
| Coil Material     | Special wire I/O |
| Power Rating      | 400 W (RMS)      |
| Nominal Impedance | 8 Ohms           |
| Surround material | Cloth            |
| Sensitivity       | 97 dB            |
| Frequency Range   | 40-3000 Hz       |
| Suspension        | Single           |
| Cone material     | Paper            |

**AP AUDIO POINT** **PD-2500PT** **18"**

Malaysian special original cone and high temperature italian wire voice coil provide you very powerful bass.

|                   |                  |
|-------------------|------------------|
| Nominal Diameter  | 487mm/18"        |
| Magnet Type       | Ferrite (4 cut ) |
| Voice Coil Dia.   | 152mm/6" I/O     |
| Coil Material     | Italian Copper   |
| Power Rating      | 2500 W (RMS)     |
| Nominal Impedance | 8 Ohms           |
| Surround material | Cloth            |
| Sensitivity       | 96 dB            |
| Frequency Range   | 30-1000 Hz       |
| Suspension        | Double Spider    |
| Cone material     | Malaysian Paper  |

**AP AUDIO POINT** **18L-1800BT**

Malaysian Original Paper Cone And Italian Voice Coil Gives You Lion Performance.


|                   |                 |  |
|-------------------|-----------------|--|
| Nominal Diameter  | 487mm/18"       | The 18L-1800BT is an excellent choice for high output subwoofer system designs where extended deep bass energy is ecified. |
| Magnet Type       | Ferrite         |  |
| Voice Coil Dia.   | 126mm/5" I/O    |  |
| Coil Material     | Italian Copper  |  |
| Power Rating      | 2000 W (RMS)    |  |
| Nominal Impedance | 8 Ohms          |  |
| Surround material | Cloth           |  |
| Sensitivity       | 96 dB           |  |
| Frequency Range   | 30-1500 Hz      |  |
| Suspension        | Double Silicone |  |
| Cone material     | Malaysian Paper |  |

**AP AUDIO POINT** **AP-1600LF**

The AP-1600LF Features a double silicone spider system ensures excellent control during large excursion.

|                   |                    |
|-------------------|--------------------|
| Nominal Diameter  | 457mm / 18"        |
| Magnet Type       | Ferrite            |
| Voice Coil Dia.   | 114.4mm / 4.5"     |
| Coil Material     | Italian copper I/O |
| Power Rating      | 1600 W (AES)       |
| Nominal Impedance | 8 Ohm              |
| Cone Material     | Malaysian Paper    |
| Surround Material | Cloth              |
| Sensitivity       | 97 dB              |
| Frequency Range   | 35-1500 Hz         |
| Suspension        | silicone Double    |

**AP AUDIO POINT** **GM-650Z**  
15" PROFESSIONAL TRANSDUCER



|                   |             |
|-------------------|-------------|
| Nominal Diameter  | 381mm / 15" |
| Chassis Type      | Aluminium   |
| Magnet Type       | Ferrite     |
| Voice Coil Dia.   | 99.3mm / 4" |
| Power Rating      | 600 W (RMS) |
| Nominal Impedance | 8 Ohm       |
| Surround Material | Cloth       |
| Sensitivity       | 97dB        |

**GM-650Z gives excellent bass and mid-bass response, High power handling capacity.**  
Italian voice coil used in this speaker for clear and best sound with stands high temperature.

**AP AUDIO POINT** **CR-1000A** **NPR SERIES**



|                   |                 |
|-------------------|-----------------|
| Nominal Diameter  | 381mm / 15"     |
| Chassis Type      | Aluminium       |
| Magnet Type       | Ferrite         |
| Voice Coil Dia.   | 99.3mm / 4"     |
| Coil Material     | CCA-R (Italian) |
| Power Rating      | 1000 W (RMS)    |
| Nominal Impedance | 8 Ohm           |
| Surround Material | Cloth           |
| Sensitivity       | 96.0 dB         |
| Frequency Range   | 55-2000 Hz      |
| Suspension        | Double          |
| Cone Material     | Malaysian Paper |

**The Power You Want**

**AP AUDIO POINT** **NPR SERIES PD15-1200A** **15"**



A double silicon spider system ensures excellent control during large excursions.

|                   |                    |
|-------------------|--------------------|
| Nominal Diameter  | 381mm/15"          |
| Magnet Type       | Ferrite            |
| Voice Coil Dia.   | 114.4/4.5"         |
| Coil Material     | Italian Copper I/O |
| Power Rating      | 1200 W (RMS)       |
| Nominal Impedance | 8 Ohms             |
| Surround material | Cloth              |
| Sensitivity       | 97 dB              |
| Frequency Range   | 30-1500 Hz         |
| Suspension        | Dual Silicon       |
| Cone material     | Paper              |

**AP AUDIO POINT** **AUDIO POINT LPR-1200 IS A VERY POWERFUL 18" WOOFER THAT HANDLES A 1200 WATTS RMS.**  
**LPR-1200**



|                   |                    |
|-------------------|--------------------|
| Nominal Diameter  | 457mm/18"          |
| Magnet Type       | Ferrite            |
| Voice Coil Dia.   | 99.3/4"            |
| Coil Material     | Italian Copper I/O |
| Power Rating      | 1200 W (RMS)       |
| Nominal Impedance | 8 Ohms             |
| Surround material | Cloth              |
| Sensitivity       | 96 dB              |
| Frequency Range   | 30-1500 Hz         |
| Suspension        | Double             |
| Cone material     | Malaysian Paper    |

**AP AUDIO POINT** **2226B-V3**



**THE 2226B-V3 IS A HIGH OUTPUT LOW FREQUENCY TO MID RANGE TRANSDUCER**

|                   |             |
|-------------------|-------------|
| Nominal Diameter  | 381mm/15"   |
| Magnet Type       | Ferrite     |
| Voice Coil Dia.   | 99.3mm/4"   |
| Coil Material     | CCAW I/O    |
| Power Rating      | 600 W (RMS) |
| Nominal Impedance | 8 Ohms      |
| Surround material | Cloth       |
| Sensitivity       | 97 dB       |
| Frequency Range   | 49-2500 Hz  |
| Suspension        | Single      |
| Cone material     | Paper       |

**AP AUDIO POINT** **YP-850**  
15" PROFESSIONAL LOUDSPEAKER



|                   |             |
|-------------------|-------------|
| Nominal Diameter  | 381mm / 15" |
| Chassis Type      | Aluminium   |
| Magnet Type       | Ferrite     |
| Voice Coil Dia.   | 99.3mm / 4" |
| Power Rating      | 800 W (RMS) |
| Nominal Impedance | 8 Ohm       |
| Surround Material | Cloth       |
| Sensitivity       | 96.0 dB     |
| Frequency Range   | 35-2500 Hz  |
| Suspension        | Double      |

The YP-850 is an excellent choice for high output.

**AP AUDIO POINT** **15" NPR SERIES PD15-1000B**



A double silicon spider system ensures excellent control during large excursions.

|                   |                         |
|-------------------|-------------------------|
| Nominal Diameter  | 381mm/15"               |
| Magnet Type       | Ferrite (Double Magnet) |
| Voice Coil Dia.   | 99.3/4"                 |
| Coil Material     | Italian Copper I/O      |
| Power Rating      | 1000 W (RMS)            |
| Nominal Impedance | 8 Ohms                  |
| Surround material | Cloth                   |
| Sensitivity       | 97 dB                   |
| Frequency Range   | 40-1500 Hz              |
| Suspension        | Dual Silicon            |
| Cone material     | Paper                   |

**AP AUDIO POINT**  
**X18-1000-B1**



|                     |                      |
|---------------------|----------------------|
| Nominal Diameter    | 457mm/18 in          |
| Power Rating        | 1000W (AES)          |
| Nominal Impedance   | 8 Ohm                |
| Sensitivity         | 97 dB                |
| Frequency           | 30 Hz                |
| Voice Coil Diameter | 99.3 mm/4 in         |
| Coil Material       | ITALIAN Copper (I/O) |
| Cone Material       | IMPORTED Paper       |
| Surround Material   | Cloth                |
| Suspension          | Single               |
| Chassis Type        | Aluminum             |
| Magnet Type         | Ferrite              |

GLASS FIBRE former voice coil for withstanding high temperature.